





CCCOMBI CRUSHER

The ultimate tool for demolition operations involving highly-reinforced concrete buildings or even metal structures. The CC series incorporates characteristics of shears and concrete crushers to ensure the delivery of unbeatable performances even in the toughest context.

- The union of **powerful cylinders** and twin pin system grant an enormous breaking and cutting force.
- The **unique design of jaws** incorporates shaped shear blades, which, together with the cutting guide, gives to the CC an incredible cutting power.
- Interchangeable teeth and blades make maintenance operations easy and quick to keep the tool at full efficiency.



• The **Speed-Valve** reduces opening

and closing time boosting productivity.

• The continuous **hydraulic rotation** enables precise positioning during in height demolitions and the double-row thrust bearing ensures high robustness and increases safety.

TECHNICAL DATA

BT CCR O

ζΕV:00	MODEL		CC35	CC65
KIF. 978/1/E 12/18 REV.00	ROTATION		360° Hydraulic	
	EXCAVATOR WEIGHT	t	30-40	60-70
	TOOL WEIGHT *	kg	3500	6650
	OPENING (MAX/MIN)	mm	1100/0	1525/0
	HEIGHT	mm	2270	3000
	HYDRAULIC WORKING PRESSURE	bar	320-350	320-350
	OIL FLOW	l/min	280-300	500-600

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice. $\frac{1}{2} \int_{-\infty}^{\infty} \frac{1}{2} \left(\frac{1}{2} \int_{-\infty}^{\infty} \frac{1}{2} \left(\frac{1}{$

* Tool weight does include Mantovanibenne top bracket.









