

MERICRUSHER

MJS-160 STG H

For versatile crushing



MERICRUSHER

MERICRUSHER

MJS-160 STG H

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of farm land
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Bolt mounted hardox liner (frame)
- Heavy duty hardox frame
- UNT Rotor with carbide cutters
- Possibility to turn the direction of the rotor

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Ice crushing
- Clearing land before seeding and planting

OPTIONS

- Push bar (fixed 3-positions)
- Rear roller (hydraulic)
- Guide plate (front fixed 3-positions)

Base machine demand

Compact loaders (skid steer)	
Mounting	SAE J2513
Hydraulic	High flow (case drain)
Power range	220-450bar 120-200 l/min
Lifting capacity	Min 1800kg / 4000 lbs
Hydraulic motor control	12 V

Technical data:

Transmission	Hydraulic
Hydraulic motor	High pressure - dual speed
Planetarygear	Brevini EM-1045
Final transmission	Gear (G-serie)
Rotor diameter / width	500 / 1610mm 20 / 63 inch
Cutter qty.	72
Working depth	250 mm / 10 inch

Main dimensions:

Length	1000 mm	39 inch
Width	1610 mm	63 inch
Height	1050 mm	41 inch
Weight	1350 kg	2980 lbs
Weight, with options	1750 kg	3860 lbs

