

## AUGER DRIVES



AUGT36VGHL D Shown

**36" MAX**  
STANDARD/TREE  
AUGER BIT SIZE

**18" MAX**  
ROCK AUGER  
BIT SIZE

1. HOSES ROUTED FROM TOP OF HOUSING FOR DEEPER DRILLING WITH 12" DIAMETER BITS
2. DIRECT DRIVE MOTOR WITH HYDRAULIC PRESSURE RELIEF PROTECTION
3. PLANETARY REDUCTION ENSURES LONGEVITY & CONSISTENT TORQUE
4. BI-DIRECTIONAL AUGER ROTATION
5. AUGT36 PROVIDES 20% MORE TORQUE FOR TOUGH DRILLING CONDITIONS

## COMMON SKID STEER CONFIGURATIONS

MODEL	OUTPUT	REC FLOW (GPM)	MAX BIT DIA	TORQUE @ 3000 PSI	SPEED @ 20 GPM	MOUNT	WT (LBS)
AUG36VGHL D	2" HEX	15-25	36"	2,730 FT-LBS	67 RPM	UNIVERSAL SKID STEER	280
AUG36VGR L D	2 9/16" ROUND	15-25	36"	2,730 FT-LBS	67 RPM	UNIVERSAL SKID STEER	280
AUGT36VGHL D	2" HEX	15-27	36"	3,345 FT-LBS	55 RPM	UNIVERSAL SKID STEER	305

Includes fully assembled auger drive with drive unit, mount, hoses, and 1/2" couplers.

## DRIVE UNIT INTERCHANGEABLE BETWEEN SKID STEERS, MINI EXCAVATORS & MINI SKID STEERS



See next page for more options >>

## BUILD YOUR OWN

Select a ...

### 1. DRIVE UNIT

View Available 3' Auger Bits on [page 124](#).

### 2. MOUNT

View Available 4' Auger Bits on [page 62](#).

### 3. HOSE KIT

View More Information for Mini Skid Steers on [page 122](#). 

View More Information for Mini Excavators on [page 132](#). 

All models below can be purchased separately.

## 1. DRIVE UNIT

<b>MODEL</b>	<b>OUTPUT</b>		<b>MODEL</b>	<b>OUTPUT</b>		<b>MODEL</b>	<b>OUTPUT</b>	
AUG30H	2" HEX		AUG36H	2" HEX		AUGHT36H	2" HEX	
AUG30R	2 9/16" ROUND		AUG36R	2 9/16" ROUND				
MODEL	REC FLOW (GPM)	MAX BIT DIA	TORQUE @ 3000 PSI	SPEED	WEIGHT (LBS)			
AUG30H	10-18	30"	2,205 FT-LBS	58 @ 14 GPM	150			
AUG30R	10-18	30"	2,205 FT-LBS	58 @ 14 GPM	150			
AUG36H	15-25	36"	2,730 FT-LBS	67 @ 20 GPM	150			
AUG36R	15-25	36"	2,730 FT-LBS	67 @ 20 GPM	150			
AUGHT36H	15-27	36"	3,345 FT-LBS	55 @ 20 GPM	175			

## 2. MOUNT

									
UNIVERSAL SKID STEER	UNIVERSAL MINI SKID	BOBCAT® MINI SKID	ASV® MINI SKID	MINI-EX FRAME					
MODEL	WEIGHT	MODEL	WEIGHT	MODEL	WEIGHT	MODEL	WEIGHT	MODEL	WEIGHT
AUGQL	125 lbs	AUGQS	70 lbs	AUGQB	90 lbs	AUGQA	100 lbs	AUGQX <sup>1</sup>	50 lbs

<sup>1</sup>Mini Excavator Bolt-On Hanger Brackets sold separately.

## 3. HOSE KIT

MODEL	LENGTH	RECOMMENDED MACHINES	WEIGHT (LBS)
HKA	64"	MINI SKID STEERS & MINI-EX	5
HKB	76"	MINI BOBCAT® & MINI-EX	5
HKC	84"	MINI ASV® & MINI-EX	5
HKD	108"	SKID STEERS & LONG ARM MINI-EX	5

NOTE: Hoses include 1/2" couplers.