

# BUCKETS

## V60 UTILITY BUCKET

Available widths 72", 78", 84", 90" & 96"

Heavily built general purpose bucket for handling dense and bulk materials.



Bucket shown with optional bolt-on edge.

**AVAILABLE EDGE OPTIONS**  
See page 88 for additional information.



**STANDARD BOLT-ON**



**SERRATED BOLT-ON**

<b>40.1"</b> DEPTH	<b>24.9"</b> HEIGHT	UP TO <b>26 CU FT</b> STRUCK CAPACITY (VARIES BY MODEL)	UP TO <b>31 CU FT</b> HEAPED CAPACITY (VARIES BY MODEL)	GREATER THAN <b>2400 LB</b> LOADER OPERATING CAPACITY
-----------------------	------------------------	--	--	---

1. HD BRACING TIES TOP TO QUICK TACH PLATE
2. EXTRA BRACE PLATE INSIDE BUCKET FOR ADDED STRENGTH
3. 3/4" x 6" WELD-ON EDGE
4. 1/2" x 4" WEAR BARS PROTECT THE BUCKET BOTTOM



MODEL	HUHV72	HUHV78	HUHV84	HUHV90	HUHV96
Width: Overall / Inside (in.)	73.5 / 71.3	79.5 / 77.3	85.8 / 83.3	91.5 / 89.3	97.5 / 95.3
Overall Height (in.)	24.9				
Depth: Overall / Inside (in.)	40.1 / 35.5				
Capacity: Struck / Heaped (cu. ft.)	19.2 / 23.0	20.9 / 25.1	22.6 / 27.1	24.3 / 29.2	26.0 / 31.2
Bucket Back Angle (degrees)	66				
Shell Thickness (in.)	0.25				
Side Plate Thickness (in.)	0.25				
Structural Wear Bars Under Bucket (1/2" x 4")	4	5	5	5	5
Approximate Weight (lbs)	720	775	815	855	890
Recommended Loader Capacity	Greater than 2400 lbs				