



DEMOLITION EQUIPMENT

HUSQVARNA DXR 315

Art.no: 970 51 76 05

DXR 315 is a powerful remote-controlled demolition robot with a telescopic arm, extending the reach for a flexible set-up. Despite its low weight and compactness it delivers a power of 27 kW, making it ideal for efficient demolition in tough environments. The outriggers are individually controlled and combined with a large footprint provides superior stability which enables high workload. Equipped with a superior remote control for safer operation and easy maneuverability. DXR 315 is a versatile machine for both the construction and process industry. Combine it with a variety of tools like hammers or our compact and versatile crushers and steel shearer. For the toughest applications we recommend our additional feature packages. For DXR 315 we offer extended hydraulic function and cylinder protection package, enhanced cooling and heat protection. This enables you to work with the machine in high ambient temperatures and with the tool in a high radiation heat. The packages can be ordered as accessories or installed direct from factory.

FEATURES



Increased performance

More than 20% increased performance in power, higher productivity and efficiency.




Safer operation

Fulfills third party approval in respect of EMC, functional safety requirements and high reliability levels (PLd) which ensures a safer work environment.



Superior remote control

Enables a pleasant experience and good operational control with high level of intuitive user-friendliness with large screen with optimised angle and adaptable to dark and bright surroundings. Enables you to work remote-controlled in the most challenging areas from a distance up to 300 m.



Live operating surveillance

The remote control delivers live information about machine status such as current, voltage, temperature as well as active faults and operating time without the need of external measuring equipment. For instant machine status, increased uptime and productivity.

TECHNICAL DATA HUSQVARNA DXR 315

Art.no: 970 51 76 05

HUSQVARNA DXR 315

MOTOR

| | |
|-------------------|----------|
| Rated input power | 36 hp |
| Frequency | 50/60 Hz |

BATTERY

| | |
|-------------------|--------|
| Battery chemistry | Li-Ion |
|-------------------|--------|

HYDRAULICS

| | |
|-------------------------|--------------|
| Oil capacity | 1,420 fl oz |
| Hydraulic oil flow | 22.5 gal/min |
| Hydraulic pressure, max | 3,626 psi |

OTHER

| | |
|--------------------------------|---|
| Factory option | Extended hydraulic function & cylinder protection |
| Telescopic arm | Yes |
| Range of wireless transmission | Up to 300 m |
| Signal transmission | Radio/cable |
| Radio | 2.4 GHz |

DIMENSIONS

| | |
|-----------------------------|---------------|
| Reach (up) | 216 in |
| Reach (forward) | 204.72 in |
| Product size length | 102 in |
| Product size width | 31 in |
| Product size height | 59 in |
| Weight | 4,696 lbs |
| Packaging length (Calc) | 119.291 in |
| Packaging width (Calc) | 37.402 in |
| Packaging height (Calc) | 75.591 in |
| Article gross weight (Calc) | 5,196.296 lbs |



View all product details on:

<https://www.husqvarnaconstruction.com/ca-en/demolition-equipment/dxr315/>



DEMOLITION ROBOT TOOLS
MG 200

Jaw opening, max:
35.4 in
Volume:
18.5 gal (US)
Weight:
373 lbs
Hydraulic oil flow:
6.6 gal/min



DEMOLITION ROBOT TOOLS
SB 202

Impact energy:
406 Joule
Weight:
463 / 492 lbs
Hydraulic oil flow:
17.43 gal/min
Impact frequency:
30 Hz



DEMOLITION ROBOT TOOLS
SB 302

Impact energy:
610 Joule
Weight:
659 lbs
Hydraulic oil flow:
21.13 gal/min
Impact frequency:
23 Hz



DEMOLITION ROBOT TOOLS
DSS 200

Jaw opening, max:
7.9 in
Weight:
408 lbs
Hydraulic oil flow:
19.8 gal/min
Cutting force:
8,404 N



DEMOLITION ROBOT TOOLS
ER 50

Weight:
419 lbs
Hydraulic oil flow:
16 gal/min
Rotation angle:
360 °
Product size width:
19.7 in



[husqvarnaconstruction.com](https://www.husqvarnaconstruction.com)