

BY PALADIN















Sweepster, by Paladin, provides high quality sweepers and replacement brushes that are durable enough to perform under the most challenging conditions. Sweepster is the industry leader in rotary brooms and offers a complete line of sweepers for every prime mover and application.





SWEEPERS





Sweepster Sweepers are capable of handling all types of material including fine dirt, gravel, mud, millings and other debris.

- The <u>only</u> waterless dust mitigation system (patented)
- Higher capacity buckets (22%) equal high performance and increased efficiency (available on selected models)
- Multiple Sweeper types:
 - ~ Angle Sweepers
 - ~ Collector Sweepers
 - ~ Collector Sweepers with waterless dust abatement (patented and exclusive to Paladin)
 - ~ Walk Behind Sweepers
 - ~ Tow Behind Sweepers
- Tool-less Quick Change Core and many other standard features





SWEEPERS BY PRIME MOVER

SKID STEER LOADERS

QCSS - SSL Angle Sweeper - Hydraulic Drive
UTILITY TRACTOR LOADERSQCTL - Utility Tractor Loader Angle Sweeper - Hydraulic Drive12CS - Utility Tractor Loader Collector Sweeper - Hydraulic Drive13VCS - Utility Tractor Loader Collector Sweeper with Waterless Dust Abatement - Hydraulic Drive13
WHEEL LOADERS AND TRUCKSHSA - High Speed Truck and Wheel Loader Angle Sweeper - Hydraulic Drive
COMPACT TRACTORS MRHL - Compact Tractor Loader Angle Sweeper - Hydraulic Drive
UTILITY TRACTORS AH/CH - Utility Tractor Angle Sweeper PTO to Hydraulic Drive
WALK BEHIND SWEEPERS WSP24 - Walk Behind Sweeper
COMPACT TOOL CARRIERS Compact Tool Carrier - Angle Sweeper - Hydraulic Drive
COMMERCIAL TURF MOWERS CTM - Compact Turf Mower Angle Sweeper - Mechanical Drive
TOW BEHIND SWEEPERSTBCP and TBH - Engine Drive Tow Behind Angle Sweepers - Hydraulic Drive
SWEEPER OPTIONS
SWEEPER WEAR PARTS



SWEEPERS

When it comes to sweeping, there are many challenges

What type of materials are you dealing with - dirt and gravel - concrete and asphalt millings - heavy debris?

How much dust will you produce while sweeping?

How efficiently can you clean-up?

Is your equipment reliable and durable?

With our wide range of sweepers, Paladin can provide the perfect solution for the prime mover you already own.

Some of the standard features of our sweepers include:

- Designed and manufactured to construction grade
- Quick attach mounts
- Durable powder coat finish
- Brush heads of varying widths, diameters, and brush material, including metal, poly and mixed sections
- Reverse flow and brush for "dust pan" sweeping
- Industrial quality motors
- Tool-less Quick Change Core available on most models



Tool-less Brush Adjustment (VS/VRS)





Hold onto brush adjustment lever. Grasp and pull T-handle quick pin out. Push lever to raise or lower brush head to desired height. Release T-handle quick pin ensuring notch is fully engaged.

Tool-less Quick Change CoreImage: Core</



After resting the sweeper on the ground, remove the pins from motor and bearing mounts



Pull out the motor and hex drive assembly. The core/brush head will fall out. Hydraulic hoses do not need to be removed.



Replace the core/brush head. Insert the motor assembly. Replace the pins. *Get back to work!*

Return to Table of Contents



Collector Sweepers - Exclusive <u>Patented</u> Feature Volumizer[®] Bar

- Included with VRS and VS models
- Directs swept material more efficiently into bucket
- Increases bucket capacity by 22% with less carry over
- Increased capacity means you will need to dump less often





A simple tool-less adjustment knob allows you to accommodate brush wear and still maintain increased bucket capacity



High Dump Feature - VRS/VS

The bucket can be raised high to dump directly into trucks and dumpsters









SPECIAL FEATURES

Exclusive *Patented* Feature for Collector Sweepers <u>Waterless</u> Dust Abatement

- VS and VCS models
- New hydraulic fan and filter assembly collects fine dust during sweeping
- <u>Significantly</u> reduces dust production from sweeping action
- No water tank or sprayer mechanism needed dust control without impractical water systems that require constant refilling
- Filter can be cleaned by actuating a switch from inside cab
- No mud or clumpy debris cleanup required
- More comfort and safety for operator no dust blowing into cab during operation




High volume hydraulic fan pulls air from the sweeping chamber filtering the dust and exhausting clean air



12 volt shaker dislodges loose debris from the filter media directly into the hopper



Waterless Dust Abatement Unit



A washable PTFE impregnated filter capable of filtering dust as small as 10 microns



A double drape system seals the sweeping chamber to the ground



Prime Mover	Product Name	Description	Application		
	QCSS Angle	SSL Angle Sweeper-Hydraulic Drive	Heavy duty cleanup		
	SB Hopper	SSL Collector Sweeper-Hydraulic Drive	Standard duty cleanup		
Skid Steers	SB Heavy Duty	SSL Collector Sweeper-Hydraulic Drive	Heavy duty cleanup, concrete and asphalt millings		
	VRS Sweeper	SSL Collector Sweeper with Dust Abatement Capability-Hydraulic Drive	Heavy duty cleanup with high capacity bucket (22% more capacity than SB Hopper) and high dump.		
	VS	SSL Collector Sweeper with Waterless Dust Abatement-Hydraulic Drive	Heavy duty cleanup with high capacity bucket (22% more capacity than SB Hopper), high dump, and waterless dust abatement		

QCSS - SSL Angle Sweeper - Hydraulic Drive



- Heavy duty cleanup
- Powered from loader hydraulics
- 10-36 GPM flow required (3000 psi)
- Quick attach mount
- 32" brush diameter
- 5', 6', 7', 8' brush widths available
- Mechanical angle standard (hydraulic optional)
- Quick change core
- Optional modular design can easily change single into dual or dual into single
- Fold away stands

Specifications - Singl	e Moto	r					
Model Number	22059	22060	22071	22072	22083	22084	22096
A. Overall Height	33.5"	33.5"	33.5"	33.5"	33.5"	33.5"	33.5"
B. Overall Width @ 0°	74.8"	74.8"	86.8"	86.8"	98.8"	98.8"	110.8"
C. Overall Length @ 0°	68.5"	68.5"	68.5"	68.5"	68.5"	68.5"	68.5"
D. Sweeping Width @ 0°	60.0"	60.0"	72.0"	72.0"	84.0"	84.0"	96.0"
E. Overall Length @ 30°	77.0"	77.0"	80.0"	80.0"	83.0"	83.0"	86.0"
F. Overall Width @ 30°	75.2"	75.2"	85.6"	85.6"	96.0"	96.0"	106.4"
G. Sweeping Width @ 30°	52.0"	52.0"	62.4"	62.4"	72.8"	72.8"	83.2"
H. Center of Gravity	33.5"	33.5"	34.3"	34.3"	35.2"	35.2"	35.9"
Weight (lbs)	793	831	852	890	915	953	1020
Flow Range (GPM)	10-18	12-25	10-18	12-25	10-18	12-25	12-25
Hydraulic Motor Displacement (C.I.)	18.3	24.9	18.3	24.9	18.3	24.9	24.9
# of Motors	1	1	1	1	1	1	1
Maximum Pressure (PSI)	3500	3000	3500	3000	3500	3000	3500
Maximum Articulation	30°	30°	30°	30°	30°	30°	30°
Brush Diameter	32"	32"	32"	32"	32"	32"	32"

Specifications - Dual Motor Model Number 22061 22073 22085 22097 A. Overall Height 33.5" 33.5" 33.5" 33.5" B. Overall Width @ 0° 74.8" 86.8" 98.8" 110.8" C. Overall Length @ 0° 68.5" 68.5" 68.5" 68.5" 84.0" D. Sweeping Width @ 0° 60.0" 72.0" 96.0" 80.0" 83.0" 86.0" E. Overall Length @ 30° 77.0" F. Overall Width @ 30° 75.2" 85.6" 96.0" 106.4" G. Sweeping Width @ 30° 52.0" 62.4" 72.8" 83.2" H. Center of Gravity 35.6" 34.0" 34.8" 36.2" Weight (lbs) 831 890 953 1020

20-36

18.3

2

3500

30°

32"

Flow Range (GPM)

Displacement (C.I.)

Maximum Pressure (PSI)

Maximum Articulation

Brush Diameter

Hydraulic Motor

of Motors

20-36

18.3

2

3500

30°

32"

20-36

18.3

2

3500

30°

32"

20-36

18.3

2

3500

30°

32"



SB Hopper - SSL Collector Sweeper - Hydraulic Drive



- Standard duty cleanup
- Direct-drive motor powered from loader hydraulics
- 10-25 GPM flow required (2,000-3,500 psi)
- 26" brush diameter
- 5', 6', 7' brush widths available
- Brush head reversible for "dust panning" debris
- Dump bucket by lifting arms
- Quick change core



Cold Planer Special Option

- Designed to clean up millings after cold planer operations
- Brush is operated in reverse to collect millings in bucket
- Brush sections are compacted dense-filled wafers optimized for clearing the millings

Specifications	SB Hopper Broom	ı	
Model Number	20559/20560	20571/20572	20583/20584
Working Width	60"	72"	84"
Overall Width	66"	78"	90"
Weight (approximate)	808 lbs	916 lbs	1,033 lbs
Brush Diameter	26"	26"	26"
Heaped Capacity	13.9 ft ³	16.8 ft ³	19.8 ft ³
Minimum Hydraulic Flow	10/14 GPM	10/14 GPM	10/14 GPM
Maximum Hydraulic Flow	18/25 GPM	18/25 GPM	18/25 GPM
PSI Range	2,000 - 3,500	2,000 - 3,500	2,000 - 3,500

Specifications Cold Planer Special							
Model Number	20560P	20572P	20584P				
Working Width	60"	72"	84"				
Overall Width	66"	78"	90"				
Weight (approximate)	840 lbs	979 lbs	1,033 lbs				
Brush Diameter	26"	26"	26"				
Heaped Capacity	13.9 ft ³	16.8 ft ³	19.8 ft ³				
Minimum Hydraulic Flow	15 GPM	15 GPM	15 GPM				
Maximum Hydraulic Flow	25 GPM	25 GPM	25 GPM				
PSI Range	2,000 - 3,500	2,000 - 3,500	2,000 - 3,500				



SB Heavy Duty - SSL Collector Sweeper - Hydraulic Drive

- Heavy duty cleanup
- Bi-directional broom sweeps forward to pick up dirt; reverses to sweep in tight areas
- No front caster wheel; works easily next to walls curbs and obstacles
- Replaceable heavy duty bolt-on cutting edge on bucket
- Optional sprinkler kit with or without 25-gallon tank
- Optional gutter brush kit with poly or wire brush







Additional steel reinforcement/welds between bolts and cutting edge and side plates



Reversible, heavy duty cutting edge



Specifications Heavy D	outy SB Hopper Broom
Model Number	20571-0022HD/20572-0022HD
Working Width	72"
Overall Width	78"
Weight (approximate)	1060 lbs
Brush Diameter	26"
Heaped Capacity	16.8 ft ³
Minimum Hydraulic Flow	10/14 GPM
Maximum Hydraulic Flow	18/25 GPM
PSI Range	2,000 - 3,500 PSI

5 wear plates on underside of hopper bin



VRS-SSL Collector Sweeper, High Capacity - Hydraulic Drive



- Volumizer[®] Bar increases bucket capacity by 22%
- High dump feature
- Tool-less brush adjustment
- Heavy duty cleanup
- Brush follows ground contour with front castor
- Powered from SSL hydraulics
- 15-25 GPM flow required
- 26" brush diameter
- 5', 6', 7' brush widths available
- Quick change core

VRS Specifications	VRS5	VRS6	VRS7
Height (overall)	31.6"	31.6"	31.6"
Width (overall)	76"	88"	100"
Length (overall)	72.5"	72.5"	72.5"
Sweeping Width	60"	72"	84"
Center of Gravity	29.5"	29.5"	29.5"
Weight (Ibs)	1,235	1,351	1,467
Flow Range (GPM)	12-25	12-25	12-25
Maximum Pressure (PSI)	3,000	3,000	3,000
Brush Diameter	26"	26"	26"
Number of Motors	1	1	1



VS - SSL Collector Sweeper with <u>Waterless</u> Dust Abatement - Hydraulic Drive

- Patented <u>waterless</u> dust abatement
- Volumizer® Bar increases bucket capacity 22%
- High dump feature
- Heavy duty cleanup
- Brush follows ground contour with front castor
- Powered from SSL hydraulics
- 15-25 GPM flow required
- 26" brush diameter
- 5', 6', 7' brush widths available
- Quick change core
- Tool-less brush adjustment



Specifications	VSS5	VSS6	VSS7				
Height (overall)	30"	30"	30"				
Width (overall)	73"	85"	97"				
Length (overall)	69"	69"	69"				
Sweeping Width	60"	72"	84"				
Sweeping Width w/ Optional Gutter Brush	72"	84"	96"				
Weight (Ibs)	1,446	1,562	1,678				
Flow Range (GPM)	15-25	15-25	15-25				
PSI Range	2,000 - 3,500	2,000 - 3,500	2,000 - 3,500				
Hopper Capacity	15 ft ³	18 ft ³	21 ft ³				
Waterless Dust Abat	ement Attac	hment Spec	ifications				
Weight (approximate)		235 lbs					
Height		6.5"					
Width	59"						
Length	26.5"						
Maximum back pressure		350 psi					



SWEEPERS FOR UTILITY TRACTOR LOADERS

Prime Mover	Product Name	Description	Application
	QCTL	Utility Tractor Loader Angle Sweeper- Hydraulic Drive	Heavy duty cleanup
Utility Tractor Loaders	CS	Utility Tractor Loader Collector Sweeper- Hydraulic Drive	Heavy duty cleanup, hydraulically-activated high dump, front mounted hopper
	VCS	Utility Tractor Loader Collector Sweeper with Waterless Dust Abatement- Hydraulic Drive	Heavy duty cleanup, hydraulically-activated high dump, front mounted hopper, waterless dust abatement

QCTL - Utility Tractor Loader Angle Sweeper - Hydraulic Drive



- Heavy duty cleanup, millings, snow removal
- Powered from loader hydraulics
- 10-36 GPM flow required
- 32" brush diameter
- 5', 6', 7' brush widths available
- Quick attach and pin-on mounts available
- Mechanical angle standard, hydraulic optional
- Quick change core

Specifications								
Model #	Width	Width @ 30°	Motors	Brush Diameter	Weight (approx.)	GPM Range		
22059	60"	54"	single	32"	793	10-18		
22060	60"	54"	single	32"	793	12-25		
22061	60"	54"	dual	32"	829	18-36		
22071	72"	64"	single	32"	852	10-18		
22072	72"	64"	single	32"	852	12-25		
22073	72"	64"	dual	32"	890	18-36		
22083	84"	75"	single	32"	915	10-18		
22084	84"	75"	single	32"	915	12-25		
22085	84"	75"	dual	32"	953	18-36		
22096	96"	85"	single	32"	982	12-25		
22097	96"	85"	dual	32"	1,022	18-36		



SWEEPERS FOR UTILITY TRACTOR LOADERS

CS - Utility Tractor Loader Collector Sweeper - Hydraulic Drive

- Heavy duty cleanup, millings, snow removal
- High dump feature activated by reversing flow
- Hopper positioned in front
- Powered from loader hydraulics
- 15-50 GPM flow required
- 26" and 32" brush diameter
- 6', 7', 8', 9' brush widths available
- Quick attach and pin-on mounts available
- Quick change core

Specifications		CS26	CS32		
Specifications	6 ft	7 ft	8 ft	8 ft	9 ft
Length (Overall, without quick coupler)	75.25"	75.25"	75.25"	80.25"	80.25"
Width (Overall)	93.0"	105.0"	117.0"	117.0"	129.0"
Sweeping Width	72.0"	84.0"	96.0"	96.0"	108.0"
Brush Diameter	26.0"	26.0"	26.0"	32.0"	32.0"
Hopper Capacity	.40 yd³	.53 yd³	.61yd³	.91yd³	1.02yd ³
Weight (Ibs)	1080	1260	1440	1705	1918
Horizontal CG (Broom lifted)	24.5"	25.5"	26.5"	30.0"	30.0"



VCS - Utility Tractor Loader Collector Sweeper with Waterless Dust Abatement - Hydraulic Drive



- Patented <u>waterless</u> dust abatement
- Heavy duty cleanup
- High dump feature activated by reversing flow
- Hopper positioned in front
- Powered from loader hydraulics
- 15-50 GPM flow required
- 26" and 32" brush diameter
- 6', 7', 8', 9' brush widths available
- Quick attach mount
- Quick change core

Specifi	cations						
Model	Sweeping Width	Overall Width	Weight (Approx)	Brush Diameter	Hopper Capacity	GPM Range	PSI Range
20374	72"	93"	1300 lbs	26"	.4 yd ³	15-25	2000-3500
20375	72"	93"	1330 lbs	26"	.4 yd ³	26-50	2000-3500
20386	84"	105"	1480 lbs	26"	.53 yd³	15-25	2000-3500
20387	84"	105"	1510 lbs	26"	.53 yd³	26-50	2000-3500
20398	96"	117"	1660 lbs	26"	.61 yd³	15-25	2000-3500
20399	96"	117"	1690 lbs	26"	.61 yd³	26-50	2000-3500
20499	96"	117"	1925 lbs	32"	.91 yd³	26-50	2000-3500
20411	108"	129"	2260 lbs	32"	1.02 yd³	26-50	2000-3500



SWEEPERS FOR WHEEL LOADERS AND TRUCKS

Prime Mover	Product Name	Description	Application
	HSA	High Speed Truck and Wheel Loader Angle Sweeper- Hydraulic Drive	High speed, heavy duty cleanup
Large Trucks and LA		Truck and Wheel Loader Angle Sweeper-Hydraulic Drive	Heavy duty cleanup
Wheel Loaders	WLA	Truck and Large Articulated Wheel Loader Angle Sweeper- Hydraulic Drive	Heavy duty cleanup
	Tow Behind	Tow Behind Angle Sweeper	Heavy duty cleanup

HSA - High Speed Truck and Wheel Loader Angle Sweeper - Hydraulic Drive



- High speed heavy duty cleanup
- Powered from loader hydraulics
- 16-80 GPM flow required (2,000-4,000 psi)
- Optional hydraulic air deflector mounts to CAT II or III 3-point hitch
- 36" brush diameter
- 12', 14', 16' brush widths available
- Select quick attach, pin-on and truck mounts available
- Hydraulic angle standard

Specifications	12	FT WIDT	гн	14	FT WID	тн	10	6 FT WID	н
Model Number	21443	21444	21445	21467	21468	21469	21491	21492	21493
A. Overall Height (IN)	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2
B. Overall Width @ 0 Degrees Angle	169.5	169.5	169.5	193.5	193.5	193.5	217.5	217.5	217.5
C. Overall Length @ 0 Degrees Angle	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1
D. Sweeping Width @ 0 Degrees Angle	144.0	144.0	144.0	168.0	168.0	168.0	192.0	192.0	192.0
E. Offset to Trail Edge @35 Degrees Angle	89.4	89.4	89.4	99.3	99.3	99.3	109.1	109.1	109.1
F. Offset to Lead Edge @35 Degrees Angle	56.3	56.3	56.3	66.1	66.1	66.1	76.0	76.0	76.0
H. Overall Width @ 35 Degrees Angle	138.8	138.8	138.8	158.5	158.5	158.5	178.2	178.2	178.2
G. Overall Length @ 35 Degrees Angle	117.4	117.4	117.4	124.3	124.3	124.3	131.2	131.2	131.2
J. Sweeping Width @ 35 Degrees Angle	117.3	117.3	117.3	136.9	136.9	136.9	156.6	156.6	156.6
Brushhead Weight (LBS)	2357	2357	2357	2525	2525	2525	2693	2693	2693
Flow Range, Min-Max (GPM)	16-40	20-60	24-80	16-40	20-60	24-80	16-40	20-60	24-80
Pressure Range, Min-Max (PSI)	3335- 4500	2555- 3500	2165- 3200	3720- 4500	2815- 3500	2360- 3200	4000- 4500	3075- 3500	2555- 3200
Hydraulic Motor Displacement (CU IN)	11.9/11.9	11.9/23.9	23.9/23.9	11.9/11.9	11.9/23.9	23.9/23.9	11.9/11.9	11.9/23.9	23.9/23.9
Maximum Articulation (DEGREES)	35	35	35	35	35	35	35	35	35
Brush Diameter (IN)	36	36	36	36	36	36	36	36	36



SWEEPERS FOR WHEEL LOADERS AND TRUCKS

LA - Truck and Wheel Loader Angle Sweeper - Hydraulic Drive

- Heavy duty cleanup
- Dual motors powered from loader hydraulics
- 20-36 GPM flow required (2,000-3,500 psi)
- Casters and parallel arm mounting to follow ground contour are included
- 32" brush diameter
- 8', 9' brush widths available
- Various quick attach and pin-on mounts available
- Mechanical angle standard, hydraulic optional
- Quick change core



Specifications	22197	22109
Max Width at 0° Articulation	106.5''	118.5''
Max Length at 0° Articulation	74.5''	74.5''
Max Width at Full Articulation	103.0''	113.0''
Max Length at Full Articulation	89.0''	92.5''
Motors	dual	dual
Brush Diameter	32.0''	32.0''
Weight (lbs.)	1,700	1,950

Range of Hydraulic Oil Flow		
Dual Motor	20 to 36 gpm	

Range of Hydraulic Oil Pressure		
Dual Motor	3500 psi	



SWEEPERS FOR WHEEL LOADERS AND TRUCKS

WLA - Truck and Large Articulated Wheel Loader Angle Sweeper - Hydraulic Drive



- Heavy duty cleanup
- Dual motors powered from loader hydraulics
- 12-60 GPM flow required (2,000-4,000 psi)
- Casters and parallel arm mounting to follow ground contour are included
- 36" brush diameter
- 10', 12' brush widths available
- Various quick attach and pin-on mounts available
- Mechanical angle standard, hydraulic optional
- Quick change core

Specifications	21319	21320	21321	21344	21345
Width	120"	120"	120"	144"	144"
Motors	dual	dual	dual	dual	dual
Brush Diameter	36"	36"	36"	36"	36"
Weight (approx)	1943 lbs	1943 lbs	1943 lbs	2332 lbs	2332 lbs
GPM Range	12-30	18-45	24-60	18-45	24-60
PSI Range	3000-4500	2300-4000	2000-3500	2300-4000	2000-3500



SWEEPERS FOR COMPACT TRACTORS

Prime Mover	Product Name	Description	Application
Compact Tractor Loaders	MRHL	Compact Tractor Loader Angle Sweeper - Hydraulic Drive	Cleanup, snow removal, pavement
Compact Tractors	MRH	Compact Tractor Angle Sweeper - Hydraulic Drive	Cleanup, snow removal, pavement
	RMRM	Compact Tractor Angle Sweeper - Mechanical 3-Point Drive	Cleanup, snow removal, pavement

Mid-range and rear mount angle sweepers

MRHL - Compact Tractor Loader Angle Sweeper - Hydraulic Drive

- General cleanup, snow removal, sidewalk cleaning
- Designed for compact tractor loaders <35hp
- Powered from tractor hydraulic system
- 26" and 30" brush diameters
- 4', 5', 6' brush widths available
- Mechanical angle standard, hydraulic optional
- Quick change core

Specification chart on next page



MRH - Compact Tractor Angle Sweeper - Hydraulic Drive



- General cleanup, snow removal, sidewalk cleaning
- Includes pump and hydraulic tank to power brush from tractor mid or rear PTO
- 26" and 30" brush diameters
- 4', 5', 6' brush widths available
- Mechanical angle standard, hydraulic optional
- Lift from tractor valve
- Quick change core

Specification chart on next page



SWEEPERS FOR COMPACT TRACTORS

RMRM - Compact Tractor Angle Sweeper - Mechanical 3-Point Drive



- General cleanup, snow removal, sidewalk cleaning
- Designed for compact tractors <30hp
- Driveline powered from rear 540
- 24" brush diameter
- 4', 5', 6' brush widths available
- Mechanical angle standard, hydraulic optional
- Lift with 3-point arms

MRH - Compact Tractor Angle Sweeper - Hydraulic Drive MRHL - Compact Tractor Loader Angle Sweeper - Hydraulic Drive RMRM - Compact Tractor Angle Sweeper - Mechanical 3-Point Drive

Model	MRH	MRHL	RMRM
Mounting Location	front	loader arms	rear
Drive	hydraulic	hydraulic	chain
Brush Width Standard	6 ft	6 ft	5 ft
Sweeping Path at 30°	64"	64"	52"
Brush Diameter	24"	24"	24"
Manual Angle Change	standard	standard	standard
Hydraulic Angle Change	optional	optional	optional
PTO required	mid or rear	hydraulic	rear 540
Brush Lift	hydraulic	loader arm	rear 3 pt.
Hydraulics Supplied	yes	optional	n/a
HP required	15 to 25	15 to 25	15 to 25
Gearbox	none	none	1 to 1
Shipping Weight (app)	700 lbs	550 lbs	425 lbs



SWEEPERS FOR UTILITY TRACTORS

Prime Mover	Product Name	Description	Application
	AH/CH Utility Tractor Angle Sweeper - PTO to Hydraulic Drive		Heavy duty cleanup, paving, milling, snow
Utility Tractors	RHFA	Utility Tractor Rear Mount Angle Sweeper - Mechanical 3-Point Drive	Cleanup, snow removal, pavement
	HR Utility Tractor High Raise Angle Sweeper - Hydraulic Drive		Heavy duty cleanup, paving, milling, snow
	RLH	Utility Tractor Rear Mount Angle Sweeper - Hydraulic Drive	Cleanup, snow removal, pavement

AH/CH - Utility Tractor Angle Sweeper PTO to Hydraulic Drive



- Heavy duty cleanup, millings, snow removal
- Designed for utility tractors AH>35hp, CH>40hp
- Powered by tractor's front PTO connected to included hydraulic pump, valve and oil tank
- Mounts to Cat I rear 3-point
- 32" brush diameter
- 5', 6', 7', 9', 9', brush widths available
- Mechanical angle standard, hydraulic angle optional
- Quick change core

	[DM18	SM18		SM28				
Model	GPM Range	PSI Range	GPM Range	PSI Range	GPM Range	PSI Range	Width	Brush Diameter	Weight (Approx)
QC5	20-36	2000-3500	10-18	2000-3500	12-25	2000-3000	60"	32"	1090 lbs
QC6	20-36	2000-3500	10-18	2000-3500	12-25	2000-3000	72"	32"	1150 lbs
QC7	20-36	2000-3500	10-18	2000-3500	12-25	2000-3000	84"	32"	1210 lbs
QC8	20-36	2000-3500			12-25	2000-3000	96"	32"	1270 lbs
QC-9	20-36	2000-3500					108"	32"	1270 lbs



SWEEPERS FOR UTILITY TRACTORS

RHFA - Utility Tractor Rear Mount Angle Sweeper -Mechanical 3-Point Drive



- Heavy duty cleanup, millings, snow removal
- Designed for utility tractors >1,000 lb. 3-point lift capacity
- Driveline powered from rear 540
- Mounts to Cat I and II rear 3-point
- 32" Brush diameter
- 5', 6', 7', 8' brush widths available
- Mechanical angle standard

RHFA Specifications	
Width with standard 6 ft brush	72"
Sweeping path	64"
Weight (lbs)	850

HR - Utility Tractor High Raise Angle Sweeper - Hydraulic Drive

- Heavy duty cleanup, millings, snow removal
- Designed for utility tractors >1,000 lb. 3-point lift capacity
- Powered by tractor rear PTO to hydraulic pump, valve and oil tank
- High raise feature lifts broom to approximately 38"
- 36" Brush diameter
- 6', 7', 8' brush widths available
- Mechanical angle standard
- Quick change core



Specificati	ons				
Model	Width	Path @ 40° Angle	Weight (Approx)	Motors	GPM Range
HR6S28	72"	54.5	1188 lbs	1	14-25
HR7D18	84"	63.5	1246 lbs	2	22-35
HR7S28	84"	63.5	1202 lbs	1	14-25
HR8D18	96"	72.75	1295 lbs	2	22-35
HR8S28	96"	72.75	1251 lbs	1	14-25



SWEEPERS FOR UTILITY TRACTORS

RLH - Utility Tractor Rear Mount Angle Sweeper - Hydraulic Drive

- Heavy duty cleanup, millings, snow removal
- Designed for utility tractors >1,000 lb. 3-point lift capacity
- Brush driven from tractor hydraulics
- Mounts to Cat I and II rear 3-point
- 32" Brush diameter
- 5', 6', 7', 8' brush widths available
- Mechanical angle standard, hydraulic optional
- Quick change core



	D	M18	SN	M18	SIV	28			
Model	GPM Range	PSI Range	GPM Range	PSI Range	GPM Range	PSI Range	Width	Brush Diameter	Weight (Approx)
QC5	20-36	2000-3500	10-18	2000-3500	12-25	2000-3000	60"	32"	1090 lbs
QC6	20-36	2000-3500	10-18	2000-3500	12-25	2000-3000	72"	32"	1150 lbs
QC7	20-36	2000-3500	10-18	2000-3500	12-25	2000-3000	84"	32"	1210 lbs
QC8	20-36	2000-3500			12-25	2000-3000	96"	32"	1270 lbs
QC-9	20-36	2000-3500					108"	32"	1270 lbs



WALK BEHIND SWEEPERS

Prime Mover	Product Name	Description	Application
Well-Dahind	WSP36	Walk Behind Angle Sweeper	Light duty cleanup, snow removal, lawn de-thatching
Walk Behind	WSP24	Walk Behind Angle Sweeper	Light duty cleanup, snow removal, lawn de-thatching

WSP24 - Walk Behind Sweeper



WSP36 - Walk Behind Sweeper

- Light duty cleanup, snow removal, lawn dethatching
- Self-propelled and powered by gasoline engine
- 24" diameter brush head, 36" wide
- 5 forward and 1 reverse speed
- Infinitely adjustable angling (20° right or left)
- Balanced operation
- Optional caster wheels available for thatching applications



WB36 Specifications

Length	70.3"
Width	41"
Height	35"
Weight	274 lbs

- Light duty cleanup, snow removal, lawn de-thatching
 Self group lad and group d by group line
- Self-propelled and powered by gasoline engine
- 14" diameter brush head, 24" wide
- Adjustable handle
- 3 x 4 tires for excellent traction in snow and turf
- 1 forward and 1 reverse speed (2mph)

WB24 Specifications

•	
Width	24"
Path@ 15° Angle	20"
Brush Diameter	14"
Brush Speed	350 rpm
Weight	133 lbs



SWEEPERS FOR COMPACT TOOL CARRIERS

Prime Mover	Product Name	Description	Application
Compact Tool Carriers	СТС	Compact Tool Carrier Angle sweeper - Hydraulic Drive	Light duty cleanup, snow removal

Compact Tool Carrier - Angle Sweeper - Hydraulic Drive

- Dethatching lawns, snow removal, cleaning sidewalks, general cleanup
- For CTC with lift capacity <1,300 lbs.
- Powered by loader hydraulics 10-16 GPM required
- 26" brush diameter
- 48" width
- Universal mounts
- Mechanical angle standard, hydraulic angle optional
- Lift from mower arms
- Quick change core



SWEEPERS FOR COMMERCIAL TURF MOWERS

Prime Mover	Product Name	Description	Application
Commercial Turf	CTM	Commercial Turf Mower Angle Sweeper- Mechanical Drive	Cleanup, dethatching lawns, snow removal, pavement
Mowers	СТН	Commercial Turf Mower Angle Sweeper- Hydraulic Drive	Cleanup, dethatching lawns, snow removal, pavement

CTM - Compact Turf Mower Angle Sweeper - Mechanical Drive



- Dethatching lawns, snow removal, cleaning sidewalks, general cleanup
- Gearbox and driveline from mower front PTO
- 24" brush diameter
- 4', 5', 6' brush widths available
- Mechanical angle standard, hydraulic angle optional
- Lift from mower arms

Specification chart on next page



SWEEPERS FOR COMMERCIAL TURF MOWERS

CTH - Commercial Turf Mower Angle Sweeper - Hydraulic Drive



- Dethatching lawns, snow removal, cleaning sidewalks, general cleanup
- Includes pump and hydraulic tank to power brush
- 26" brush diameter
- 4', 5', 6' brush widths available
- Mechanical angle standard, hydraulic angle optional
- Lift from mower arms
- Quick change core

CTH - Commercial Turf Mower Angle Sweeper - Hydraulic Drive CTM - Compact Turf Mower Angle Sweeper - Mechanical Drive

Model	СТН	СТМ	
Mounting Location	front	front	
Drive	hydraulic	chain	
Brush Width Standard	5 ft	5 ft	
Sweeping Path at 30°	52"	52"	
Brush Diameter	24"	24"	
Manual Angle Change	standard	standard	
Hydraulic Angle Change	optional optional		
PTO required	front	front	
Brush Lift	mower lift	mower lift	
Hydraulics Supplied	yes	n/a	
HP required	15 to 30	15 to 30	
Gearbox	none	3 to 1	
Shipping Weight (app)	600 lbs	550 lbs	



TOW BEHIND SWEEPERS

Prime Mover	Product Name	Description	Application
Trucks and Utility Loaders	Tow Behind	Tow Behind Angle Sweeper	Heavy duty cleanup

TBCP and TBH - Engine Drive Tow Behind Angle Sweepers -Hydraulic Drive

- Heavy duty cleanup
- Gasoline and diesel sweepers powering single and dual hydraulic motor units
- 22hp (TBCP) and 32hp (TBH) air cooled engines
- 32" brush diameter
- 7', 8', 9' brush widths available depending upon model
- Multiple brush configurations available
- Quick change core



TBCP Specifications	TBCP7	TBCP8
Width	84"	96"
Brush Diameter	32"	32"
Weight (Ibs. approx)	2,500	2,600

TBH Specifications	TBH7	TBH8	TBH9
Width	84"	96"	108"
Brush Diameter	32"	32"	32"
Weight (lbs. approx)	2,500	2,600	2,700
Diesel Weights (lbs.)	2,850	2,900	2,950

TD - Tow Behind Angle Sweeper - Traction Drive from Sweeper Rear Wheels



- Heavy duty cleanup
- Sweeper rear wheels power brush head
- Two speed gearbox (high and low)
- 32" brush diameter
- 7', 8', 9' brush widths available depending upon model
- Manual angle
- Multiple brush configurations available
- Quick change core



TOW BEHIND SWEEPERS

TBTH - Tow Behind Angle Sweeper - Hydraulic Drive from Tow Vehicle Hydraulic System



- Heavy duty cleanup
- Tow vehicle hydraulic system powers dual hydraulic brush motors
- Requires 17 GPM @ 2,000 psi
- 32" brush diameter
- 7', 8', 9' brush widths available
- Multiple brush configurations available
- Quick change core

Model Number	TBTH7	TBTH8	TBTH9
Width	84"	96"	106"
Brush Diameter	32"	32"	32"
Weight (lbs. approx)	2,300	2,400	2,500

TBTD - Tow Behind Angle Sweeper - Tractor Driven Hydraulic Brush Drive

- Heavy duty cleanup
- Sweeper rear wheels connected to an onboard hydraulic pump, valve and tank power hydraulic motor on brush head
- 32" brush diameter
- 7' brush width available
- Multiple brush configurations available
- Quick change core

Model Number	TBTD7	TBTD8	TBTD9
Width	84"	96"	108"
Brush Diameter	32"	32"	32"
Weight (Ibs. approx.)	3,340	3,440	3,540





SWEEPER OPTIONS

Sweepster has many options for the various sweepers they offer:

- Dirt Deflectors and 180° hoods
- Hydraulic angle
- Caster wheels
- Storage stands
- Sprinkler kits
- Independent hydraulic system pump drives
- Site indicators (flags and balls)
- Gutter brushes (collector sweepers only) with wire or polypropylene bristles



SWEEPER WEAR PARTS



Sweepster supplies a full line of replacement brushes for all your sweeping needs:

- Replacement brush sections and brush sets
- Gutter brush
- Sweeper skirting (collector sweepers)
- Air filter (waterless dust abatement sweepers)

PALADIN. POWERPUL ATTACHMENT TOOLS BRADCO CP CUSTONWORKS CUIS FFC HARLEY JEWELL KODIAK J:B MCMILLEN SWEEPSTER The Power of Combined Excellence'



You Tube

in.